



BETAETIGER AZ/AZM 415-B2

- Particularly suitable for hinged guards
- For very small actuating radii in line with the plane of the actuator

Data

Ordering data

Product type description	BETAETIGER AZ/AZM 415-B2
Article number (order number)	101144796
EAN (European Article Number)	4030661134307
eCl@ss number, Version 9.0	27-27-26-06
eCl@ss number, Version 11.0	27-27-26-06
ETIM number, version 7.0	EC001487
ETIM number, version 6.0	EC001487

General data

Gross weight	160 g
--------------	-------

Mechanical data

Actuating radius, minimum	250 mm
---------------------------	--------

Actuator	straight flexible
Shearing force	25,000 N

Notes

Note (General)

The axis of the hinge must be 36 mm above and in a parallel plane to the top surface of the safety switch.

The sockets are equipped with pin holes. The use of dowel pins prevents disassembly of the actuator. By the adjustment of the hexagon socket screws "a", the actuators can be fitted any desired position. This actuator can also be used for sliding doors.

Actuating radius adjustable, minimum 250, using an hexagonal key wrench 4 A/F

Documents

Operating instructions and Declaration of conformity

AZ/AZM 415 Actuator (148.2 kB, 10.05.2019, Revision M)


Pictures

Product picture (catalogue individual photo)




ID: kaz41f13
| 281.7 kB | .jpg | 352.778 x 352.778 mm - 1000 x 1000 px - 72 dpi
| 20.9 kB | .png | 74.083 x 74.083 mm - 210 x 210 px - 72 dpi

Dimensional drawing actuator



ID: 1azm4b02
| 10.0 kB | .png | 74.083 x 51.506 mm - 210 x 146 px - 72 dpi
| 116.7 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695 px - 72 dpi

Dimensional drawing miscellaneous




ID: 5azm4b04

| 50.3 kB | .cdr |

| 130.0 kB | .jpg | 352.778 x 206.375 mm - 1000 x 585 px - 72
dpi

Actuating radius



ID: kazm4r02

| 18.3 kB | .cdr |

Schmersal India Pvt. Ltd., Plot No - G-7/1, Ranjangaon MIDC, Tal. - Shirur, Dist.- Pune 412 220

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/01/2022, 5:39 am