



BNS 33-02Z-ST-2187

- Individual contact outlet
- Connector M8 x 1, 4-pole
- Thermoplastic enclosure
- Concealed mounting possible
- Insensitive to transverse misalignment
- 88 mm x 25 mm x 13 mm
- Long life
- no mechanical wear
- Insensitive to soiling

Data

Ordering data

Product type description	BNS 33-02Z-ST-2187
Article number (order number)	101173053
EAN (European Article Number)	4030661301990
eCl@ss number, Version 9.0	27-27-24-02
eCl@ss number, Version 11.0	27-27-24-02
ETIM number, version 7.0	EC002544
ETIM number, version 6.0	EC002544

Approval - Standards

Certificates	TÜV EAC
--------------	------------

General data

Standards	IEC 60947-5-3 BG-GS-ET-14
Coding level according to ISO 14119	Low
Active principle	Magnetic drive

Installation conditions (mechanical)	not flush
Enclosure material	Glass-fibre, reinforced thermoplastic
Gross weight	35 g

General data - Features

Prerequisite evaluation unit	Yes
Number of openers	2

Safety appraisal

Standards	EN ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	25,000,000 Operations
-----------------------------------	-----------------------

Mechanical data

Active area	lateral
Actuating element	Magnet
Repeat accuracy R	$\leq 0.1 \times S_{ao}$
Direction of motion	Head-on to the active surface

Mechanical data - Switching distances according IEC 60947-5-3

Ensured switch distance "ON" S_{ao}	5 mm
	8 mm
Ensured switch distance "OFF" S_{ar}	15 mm
	18 mm

Mechanical data - Connection technique

Terminal Connector	Connector M8
--------------------	--------------

Mechanical data - Dimensions

Length of sensor	13 mm
Width of sensor	88 mm
Height of sensor	25 mm

Ambient conditions

Degree of protection	IP67
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+70 °C
Storage and transport temperature, minimum	-25 °C
Storage and transport temperature, maximum	+70 °C
Resistance to vibrations to EN 60068-2-6	10 ... 55 Hz, amplitude 1 mm
Resistance to shock	30 g / 11 ms

Electrical data

Voltage type	AC (alternating current) DC (direct current)
Switching voltage, maximum	60 VAC
Switching current, maximum	0.25 A
Switching capacity, maximum	5 W
Switching frequency, maximum	5 Hz

Electrical data - Digital Output

Versions	Miscellaneous, Reed contacts
----------	------------------------------

Scope of delivery

Included in delivery	Actuators must be ordered separately.
----------------------	---------------------------------------

Accessory

Recommendation (actuator)	BPS 33-2326
---------------------------	-------------

Recommended safety switchgear	SRB 219IT SRB 308IT SRB-E-301ST SRB-E-201LC
-------------------------------	--

Notes

Note (General)	Contact symbols shown for the closed condition of the guard device. The contact configuration for versions with or without LED is identical.
----------------	---

Ordering code

Product type description:
BNS 33-(1)Z(2)-(3)-(4)

(1)	
02	2 NC contact
11	1 NO contacts/1 NC contact
12	1 NO contact/2 NC contacts
(2)	
without	without LED switching conditions display
G	with LED switching conditions display
(3)	
without	with cable
ST	with connector M8
(4)	
2187	Individual contact outlet
2187-10	Individual contact outlet with LED
2237	Actuation from cable direction

Pictures

Product picture (catalogue individual photo)




ID: kbns3f21

| 129.8 kB | .jpg | 232.833 x 105.481 mm - 660 x 299 px - 72 dpi

| 23.0 kB | .png | 74.083 x 33.514 mm - 210 x 95 px - 72 dpi

Dimensional drawing basic component




ID: 1bns3g06

| 93.7 kB | .cdr |

| 3.9 kB | .png | 74.083 x 52.211 mm - 210 x 148 px - 72 dpi

| 80.9 kB | .jpg | 352.778 x 248.003 mm - 1000 x 703 px - 72 dpi

Diagram




ID: kbns3k22

| 19.2 kB | .cdr |

| 126.8 kB | .jpg | 352.778 x 404.283 mm - 1000 x 1146 px - 72 dpi

Characteristic curve




ID: kbns3a01

| 13.1 kB | .png | 74.083 x 45.508 mm - 210 x 129 px - 72 dpi

| 124.5 kB | .jpg | 352.778 x 216.253 mm - 1000 x 613 px - 72 dpi

Contact arrangement



ID: km8--k4b

| 17.0 kB | .cdr |

Schmersal India Pvt. Ltd., Plot No - G-7/1, Ranjangaon MIDC, Tal. - Shirur, Dist.- Pune 412 220

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

