



T5C 236-11Z-M20

- 1 Cable entry M 20 x 1.5
- Thermoplastic enclosure
- Double-insulated
- Good resistance to oil and petroleum spirit
- 30 mm x 88,5 mm x 30 mm
- Actuator heads can be repositioned by 4 x 90°

Data

Ordering data

Product type description	T5C 236-11Z-M20
Article number (order number)	101153304
EAN (European Article Number)	4030661168937
eCl@ss number, Version 9.0	27-27-06-09
eCl@ss number, Version 11.0	27-27-06-09
ETIM number, version 7.0	EC002591
ETIM number, version 6.0	EC002591

Approval - Standards

Certificates	cULus
	CCC
	EAC

General data

Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the actuator	Stainless steel
Material of the contacts, electrical	Silver
Gross weight	90 g

General data - Features

Number of auxiliary contacts	1
Number of safety contacts	1

Safety appraisal

Standards	BG-GS-ET-15 EN ISO 13849-1 EN 60947-5-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	20,000,000 Operations
-----------------------------------	-----------------------

Mechanical data

Actuating element	Swivel lever
Mechanical life, minimum	1,000,000 Operations
Positive break angle	12.5 °
Positive break torque	0.2 Nm
Opening angle	180°

Mechanical data - Connection technique

Terminal Connector	Screw terminals M20 x 1.5
Cable section, minimum	1 x 0.75 mm ²
Cable section, maximum	1 x 2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Length of sensor	30 mm
Width of sensor	93 mm

Height of sensor	94.5 mm
------------------	---------

Height of the actuator	78 mm
------------------------	-------

Ambient conditions

Degree of protection	IP67
----------------------	------

Ambient temperature, minimum	-30 °C
------------------------------	--------

Ambient temperature, maximum	+80 °C
------------------------------	--------

Ambient conditions - Insulation value

Rated insulation voltage U_i	500 V
--------------------------------	-------

Rated impulse withstand voltage U_{imp}	6 kV
---	------

Electrical data

Thermal test current	10 A
----------------------	------

Utilisation category AC-15	230 VAC
----------------------------	---------

Utilisation category AC-15	4 A
----------------------------	-----

Utilisation category DC-13	24 VDC
----------------------------	--------

Utilisation category DC-13	1 A
----------------------------	-----

Switching element	NO contact, NC contact
-------------------	------------------------

Switching principle	Creep circuit element
---------------------	-----------------------

Switching frequency	5,000 /h
---------------------	----------

Ordering code

Product type description:
T(1)C 236-(2)Z-(3)

(1)	
3	left-hand model
4	Swing-door version
5	right-hand model
(2)	
01	1 NC contact
02	2 NC contact
11	1 NO contacts/1 NC contact
(3)	
without	Cable entry M20
ST	M12 connector with A-coding
ST-2310	M12 connector with B-coding


Pictures

Product picture (catalogue individual photo)




ID: k2363f02
| 213.8 kB | .jpg | 102.658 x 248.003 mm - 291 x 703 px - 72 dpi
| 162.0 kB | .png | 74.083 x 178.858 mm - 210 x 507 px - 72 dpi

Dimensional drawing basic component



ID: 1c236g01
| 31.6 kB | .cdr |
| 8.5 kB | .png | 74.083 x 51.506 mm - 210 x 146 px - 72 dpi
| 104.4 kB | .jpg | 352.778 x 245.886 mm - 1000 x 697 px - 72 dpi

Dimensional drawing actuator




ID: 1c235b03

| 3.0 kB | .png | 74.083 x 52.211 mm - 210 x 148 px - 72 dpi

| 57.4 kB | .jpg | 352.778 x 248.003 mm - 1000 x 703 px - 72 dpi

Switch travel diagram




ID: kc235s07

| 18.9 kB | .cdr |

| 1.9 kB | .png | 74.083 x 25.4 mm - 210 x 72 px - 72 dpi

| 54.5 kB | .jpg | 352.778 x 120.297 mm - 1000 x 341 px - 72 dpi

Diagram



ID: k1o1sk01

| 52.2 kB | .jpg | 352.778 x 143.581 mm - 1000 x 407 px - 72 dpi

Schmersal India Pvt. Ltd., Plot No - G-7/1, Ranjangaon MIDC, Tal. - Shirur, Dist.- Pune 412 220

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 12/01/2022, 6:09 pm